



*** PINOUT DIAGRAM ***

J1	OPEN	J1	OPEN
1	BLACK	21	BLACK/WHITE
2	BROWN	22	BROWN/WHITE
3	RED	23	RED/WHITE
4	ORANGE	24	ORANGE/WHITE
5	GREEN	25	GREEN/WHITE
6	PURPLE	26	PURPLE/WHITE
7	BLUE	27	BLUE/WHITE
8	GRAY	28	GRAY/BLACK
9	LIGHT GREEN	29	LIGHT GREEN/BLACK
10	YELLOW	30	YELLOW/BLACK
11	PINK	31	PINK/BLACK
12	LIGHT BLUE	32	LIGHT BLUE/BLACK
13	PINK/RED	33	PINK/GREEN
14	LIGHT BLUE/RED	34	LIGHT BLUE/GREEN
15	GRAY/RED	35	GRAY/GREEN
16	LIGHT GREEN/RED	36	LIGHT GREEN/GREEN
17	PINK/BLUE	37	LIGHT BLUE/BLUE
18	PURPLE/BLACK	38	BLUE/BLACK
19	RED/BLACK	39	ORANGE/BLACK
20	WHITE	40	GREEN/BLACK

SPECIFICATIONS:

1. WITHSTAND 500VAC 1 MIN OR 600VAC 1 SEC
2. MAXIMUM OPERATING CURRENT 32A PER CABLE.
3. RATED 32 CONDOUCTORS AT 0.5A PLUS 8 CONDUCTORS 2.0A.
4. RATED 32 CONDOUCTORS AT 0.3A PLUS 4 CONDUCTORS AT 2.4A.
5. MAXIMUM WORKING VOLTAGE=30V AC/DC.
6. MAXIMUM AMBIENT TEMPERATURE 60°C.
7. MINIMUM BEND RADIUS 3.15 [80]
8. CABLE DIAMETER .39 [10]

⑤	LABEL+UL CLEAR HEAT SHRINK TUBE(□□11.0mm, L:50mm)
④	BLACK HEAT SHRINK TUBE(∅11.0mm),L=24mm
③	FUJITSU SOLDERING TYPE JACK FCN-360 SERIES PART NUMBER FCN-361J040-AU
②	FUJITSU LOW PROFILE COVER(OBTUSE ANGLE CABLE-OUT) TYPE J2 PART NUMBER FCN-360C040-J2(40 CONTACTS).
①	UL2464 24AWG*40C+PAPER CABLE OD: 10.0mm, JACKET BLACK COLOR.
NO	MATERIAL SPECIFICATION

PART NO.	LENGTH
ZL-D24-CBL40-1XP	3.3' [1.0M]
ZL-D24-CBL40-2XP	6.6' [2.0M]

ZL-D24-CBL40-nXP

Units: inches [mm]
 Full Scale
 () denotes # of similar objects
 ∅ denotes diameter