

# Edison Fuses – Fuse Holders

## Features

- Multiple-pole configurations
- Finger-safe protection
- Optional “open-fuse” indication
- Polyester material is UL 94V-0 rated, self-extinguishing
- Multi-phase connections available for ganging poles
- CE marking

## Application

CHM: Edison MCL, MOL, MEQ, MEN midjet fuses.

CHCC: Edison HCLR, HCTR, EDCC fuses



### Agency Approvals Class CC

- UL Listed to 512, Guide IZLT, File E14853
- CSA Certified, Std. C22.2 No. 39, Class 6225-01, File LR47235
- IEC 60269
- IEC 60947
- CE Compliant

### Agency Approvals Midget

- UL Recognized to 512, Guide IZLT2, File E14853
- CSA Certified, Std. C22.2 No. 39, Class 6225-01, File LR47235
- IEC 60269
- IEC 60947
- CE Compliant

| Modular Fuseholder Selection Table |  |     |    |     |                     |                       |                                |          |                |                                  |          |                |                                |                   |
|------------------------------------|--|-----|----|-----|---------------------|-----------------------|--------------------------------|----------|----------------|----------------------------------|----------|----------------|--------------------------------|-------------------|
| Series Size                        | Max Voltage & Current                            | IEC | UL | CSA | Phase Configuration | No. of 17.5mm Modules | Fuse Holder Without Indication | Box Qty. | Pc. Wt. (lbs.) | Fuse Holder with Neon Indication | Box Qty. | Pc. Wt. (lbs.) | Wire Range                     | Maximum Torque    |
| CHM Midget Class                   | UL/CSA 600 VAC/DC, 30A (3 Watt) IEC 690 VAC, 32A | •   | †  | •   | 1 pole              | 1                     | CHM1D                          | 12       | 0.14           | CHM1DI                           | 12       | 0.14           | 1-16mm <sup>2</sup> (18-8 AWG) | 2.5 Nm (22 lb-in) |
|                                    |  | •   | †  | •   | 2 pole              | 2                     | CHM2D                          | 6        | 0.3            | CHM2DI                           | 6        | 0.3            |                                |                   |
|                                    |  | •   | †  | •   | 3 pole              | 3                     | CHM3D                          | 4        | 0.4            | CHM3DI                           | 4        | 0.4            |                                |                   |
| CHCC Class CC                      | UL/CSA 600VAC/DC, 30A                            |     | †† | •   | 1 pole              | 1                     | CHCC1D                         | 12       | 0.14           | CHCC1DI                          | 12       | 0.14           |                                |                   |
|                                    |  |     | †† | •   | 2 pole              | 2                     | CHCC2D                         | 6        | 0.3            | CHCC2DI                          | 6        | 0.3            |                                |                   |
|                                    |  |     | †† | •   | 3 pole              | 3                     | CHCC3D                         | 4        | 0.4            | CHCC3DI                          | 4        | 0.4            |                                |                   |

• Holder width as compared to standard 17.5mm module (1 = 17.5mm, 2 = 35mm)

† UL Recognized

†† UL Listed

## Fuse Holders Dimensions

mm[inches]

